

Product Specifications G5X0 Desktop Printer

Model	G500		G530	
Print Method	Thermal Transfer/Direct Thermal			
Resolution	203 dpi (8 dot/mm)		300 dpi (12 dots/mm)	
Print Speed	5 IPS (127 mm/s)		4 IPS (102 mm/s)	
Print Width	4.25" (108 mm)		4.16" (105.7 mm)	
Print Length	Min. 0.16" (4 mm)**; Max. 68" (1727 mm)		Min. 0.16" (4 mm)**; Max. 30" (762 mm)	
Memory	Flash	8 MB Flash (4 MB for user storage)		
	SDRAM	16MB		
Sensor Type	Adjustable reflective sensor 2 fixed transmissive sensors, central aligned			
Media	Types	Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming		
	Width	1" (25.4 mm) Min. - 4.64" (118 mm) Max.		
	Thickness	0.003" (0.06 mm) Min. - 0.01" (0.25 mm) Max.		
	Label Roll Diameter	Max. 5" (127 mm)		
	Core Diameter	1", 1.5", 3" (25.4 mm, 38.1 mm, 76.2 mm)		
Ribbon	Types	Wax, wax/resin, resin		
	Length	981' (300 m)		
	Width	1.18" Min. - 4.33" (30 mm - 110 mm) Max.		
	Ribbon Roll Diameter	2.67" (68 mm)		
Core Diameter	1" (25.4 mm)			
Printer Language	EZPL, GEPL, GZPL auto switch			
Software	Label Design Software	QLabel-IV / GoLabel (for EZPL only)		
	Driver	Windows 2000, XP, Vista, 7, Windows Server 2003 & 2008		
	DLL	Windows 2000, XP and Vista		
Resident Fonts	Bitmap Fonts	6, 8, 10, 12, 14, 18, 24, 30, 16x26 and OCR A&B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical directions		
	Scalable Fonts	90°, 180°, 270° rotatable		
Download Fonts	Bitmap Fonts	90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable		
	Scalable Fonts	90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions		
Barcodes	1-D Bar Codes	Code 39, Code 93, EAN 8 /13 (add on 2 & 5), UPC A/E (add on 2 & 5), I 2 of 5 & I 2 of 5 with Shipping Bearer Bars, Codabar, Code 128 (subset A, B, C), EAN 128, RPS 128, UCC 128, UCC/EAN-128 K-Mart, Random Weight, Post NET, IIF 14, China Postal Code, HIBC, MSI, Plessey, Telepen, FIM, GS1 DataBar		
	2-D Bar Codes	PDF417, Datamatrix code, MaxiCode, QR code, Micro PDF417, Micro QR code, Aztec code		
Code Pages	Codepage 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737 Windows 1250, 1251, 1252, 1253, 1254, 1255, 1257 Unicode (UTF8, UTF16)			
Graphics	Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software			
Interfaces	USB	USB	USB	USB
	Parallel	Serial	Parallel	Serial
		Ethernet		Ethernet
Control Panel	Two bi-color status-LEDs: Ready, Status Control key: FEED			
Power	Auto Switching 100-240VAC, 50-60Hz			
Environment	Operation Temperature	41°F to 104°F (5°C to 40°C)		
	Storage Temperature	-4°F to 122°F (-20°C to 50°C)		
Humidity	Operation	30-85%, non-condensing		
	Storage	10-90%, non-condensing		
Agency Approvals	CE (EMC), FCC Class A, CB, CCC			
Dimension	Length	11.2" (285 mm)		
	Height	6.8" (171 mm)		
	Width	8.9" (226 mm)		
Weight	6 lbs (2.72 Kg), excluding consumables			
Options & Accessories	Cutter module			
	Label Dispenser			
	External label roll holder for 10" (250 mm) O.D. label rolls			
	External label rewinder			

* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.
 ** Minimum print height specification compliance can be dependent on non-standard material variables such as label type, thickness, spacing, liner construction, etc.
 Godex is pleased to test non-standard materials for minimum height printing capability.



www.godexintl.com

Godex Europe GmbH, Industriestrasse 19, D-42477 Radevormwald, Geschäftsführer: Roy Theisen, Barry Stuart Rose,
 Handelsregister-Nr. HRB 50788, Amtsgericht Köln, Ust.-IdNr. DE813195023, Steuer-Nr. 221/5743/2628, WEEE Reg.-Nr. DE45355452.